Windsor Plywood'sPREHUNG DOOR WORK ORDER

Order #:_	
Date: -	
Date Required: -	

	`			• · · · · · · · ·			Require	ed: —	
Customer I	Name [.]					Phone			_ Fax:
	Customer Name: Invoice #:								
P.O.#:			In	voice #:		_ Sales	Person:		
					_				
QTY.	INT.	EXT.		DOOR STYI	_E			GL	ASS STYLE
			ı				I		
			SE	LECT DOOR AN	ID SIDELIT	E COM	IBINATIONS		
		*				*			
Door Size			or Size & R.O. Size*	Door Size & R.O. Size*	Door Size & R.0	O. Size*	Door Size & R.O. Si	-	Door Size & R.O. Size*
	20" x 82.5" 26" x 82.5"						1'6" = 42.5" x 82.5" 2'0" = 50.5" x 82.5"	_	
2'4" = 3	30" x 82.5"						2'4" = 58.5" x 82.5"		
	32" x 82.5"	-	2'6" = 47.5" x 82.5"	2'6" = 47.5" x 82.5"	2'6" = 63" x 82	+	2'6" = 62.5" x 82.5"	-	2'6" = 93.25" x 82.5"
	34" x 82.5" 36" x 82.5	$\dashv =$	2'8" = 49.5" x 82.5" 2'10" = 51.5" x 82.5"	2'8" = 49.5" x 82.5" 2'10" = 51.5" x 82.5"	2'8" = 65" x 82 2'10" = 67" x 8	+	2'8" = 66.5" x 82.5" 2'10" = 70.5" x 82.5		2'8" = 97.25" x 82.5" 2'10" = 101.25" x 82.5"
			3'0" = 53.5" x 82.5"	3'0" = 53.5" x 82.5"	3'0" = 69" x 82		3'0" = 74.5" x 82.5"	-	3'0" = 105.25" x 82.5"
Other:			Other:	Other:	Other:		Other:		Other:
allow 1-1/2	" under d	loor for f	looring. If you want le	w wood stud to stud meases clearance under the consideration of the cons	door you must trim	EFT HAN	m raw header to Plywom of the jamb legs. (To INSWING ISIDE TSIDE	rood o	r concrete floor. Please note we ill drop the door height) LEFT HAND OUTSWING INSIDE OUTSIDE
	MB SIZE		JAMB ST		Standard		HINGE SIZE		HINGE COLOUR
=	-9/16"		Primed		NRP		3-1/2"		Brass (3)
	-9/16"		Compos	ite	Self Close		4"		Chrome (26)
Othe	7-1/4" 		Other:		Ball Bearing		Other:		☐ Brushed Chrome (26D)
Guile	,,,				Other:				Satin Nickel (15)
N/E ATI	UEDOTO	up.	DOOD CW		NIII OTVIE		DDIOKMOU!! D		Antique Nickel (15A)
	HERSTR White	IIP	DOOR SW White		SILL STYLE luminum/Oak		BRICKMOULD		
	Brown		Brown		Fir		1-3/8"		Oil Rubbed Bronze (10B)
	Black		Black		Other:		2-1/4"		Other:
Sin	CKSET gle Drill uble Drill		2-3/4"		ASTRAGAL Aluminum Fir Primed		FOR INTERIOR DOUBLE DOORS Roller Catch Flush Bolt		All claims for errors and damage must be placed within 48 hours from receipt of materials. Any change to this order must be done in person and initialled. No changes will be accepted
			Other:		Other:				over the phone.
SPECIAL INSTRUCTIONS:					I acknow	vledge that all the info	rmatio	n shown on this sheet is accurate.	
						Custome	er		
						Approva			
						D			